

Rótula SI

BRF16-60-502-DURBAL - BRF16-60-502-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/brf16-60-502-durbal>

BRF16-60-502



DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished

inner ring:
stainless steel, hardened, surface superfinished

lubrication:
aluminium-complex soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]										
type	right-hand thread	left-hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	b ₁	b ₂	h
BRF 16 -60	-502		16	22,0	M 16	19,0	42	27	21	15,0	64	

measurements [mm]			weight	calculation-factors	rotational speed limit	basic load rating				
type	l ₁	l ₂	SW	α [°]	Y	v ₀	C	stat. C ₀ [N]		
BRF 16	28	8,0	22	8,0	0,224	2,24	2,35	975	4250	1600

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952509297
Diâmetro interior	16 mm
Diâmetro exterior	42 mm
Espessura	21 mm
Tipo	SI
Peso	224 g
Linha	Rosca esquerda
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE