

Rótula SI

BRF20-60-501-DURBAL - BRF20-60-501-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/brf20-60-501-durbal>

BRF20-60-501



DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing: stainless steel 1.4034, hardened, bearing race superfinished

inner ring: stainless steel, hardened, surface superfinished

lubrication: aluminium-complex soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting: DIN 3405 D1/A (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

bearing clearance: 10 - 30 µm radial

tolerances: see page 10

female thread: long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]										
type	light load thread	light load thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	b ₁	b ₂	h
BRF 20 -60	-501		20	27,5	M 20 x 1,5	24,5	50	34	25	18,0	77	
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating				
type	l	l ₁	l ₂	SW	α [°]	Y	l ₀	n _{max} [min ⁻¹]	d _{yn} [N]	stat. C ₀ [N]		
BRF 20	33	10,0	26	30	7,0	0,367	2,46	2,58	825	5350	2300	

CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952509310
Diâmetro interior	20 mm
Diâmetro exterior	50 mm
Espessura	25 mm
Tipo	SI
Peso	367 g
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE