

# Rótula SI

## BRF1-1-00-501-DURBAL - BRF1-1-00-501-DURBAL

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/brf1-1-00-501-durbal>

### BRF1/1-00-501



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminum complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3405 D1/A (sizes 1/4 and 3/8)  
DIN 71 412 H1 (sizes 1/2 and 1 1/4)

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**female thread:**  
long-term lubrication, low maintenance, shields, dimensions in inches

order number		measurements [inches]										
type	right hand thread	left hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	d <sub>7</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>
BRF 1/1 -00	-501		1.000	1.171	1.0000-12 UNF	1.161	2.519	1.377	1.220	.866		
measurements [inches]		weight	calculation factors	rotational speed limit	basic load rating							
type	h	l	l <sub>1</sub>	l <sub>2</sub>	SW	α [°]	Y	Y <sub>max</sub>	rpm	C	C <sub>0</sub>	
BRF 1/1	3.720	1.653	.236	1.279	1.181	5.0	0.570	2.02	2.12	600	11030	5680

## CARACTERÍSTICAS DO PRODUTO

Marca	DURBAL
Nº Ean13	3663952510217
Diâmetro interior	25.4 mm
Diâmetro exterior	63.98 mm
Espessura	30.99 mm
Tipo	SI
Peso	570 g
Linha	Rosca direita
Lubrificação	com
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE