


Casquilho de agulhas FCL-10-K-NADELLA - FCL-10-K-NADELLA

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/fcl-10-k-nadella>

Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F _o mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min	Suitable needle bush
10	FCL-10-K	10	14	12	4.60	19000	HK1010

Shaft Ø mm	Gaging			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Mounting		Max. mm	Min. mm	
10	13.980	9.976	10.005	20	Max. mm	Min. mm	Max. mm	Min. mm	0.004

CARACTERÍSTICAS DO PRODUTO

Marca	NADELLA
Nº Ean13	3616060472519
Diâmetro interior	10 mm
Diâmetro interior	0.394" inch
Diâmetro exterior	14 mm
Diâmetro exterior	0.551" inch
Espessura	12 mm
Espessura	0.472" inch
Peso	4 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE