

## Casquilho de agulhas FC-20-NADELLA - FC-20-NADELLA

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/fc-20-nadella>

### Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F <sub>0</sub> mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min*	Suitable needle bush
20	FC-20	20	26	16	32.6	11000	HK2012

Shaft Ø mm	Gaging			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Mounting		Max. mm	Min. mm	
20	25.976	19.970	20.007	38	Max. mm	Min. mm	Max. mm	Min. mm	0.021

## CARACTERÍSTICAS DO PRODUTO

Marca	NADELLA
Nº Ean13	3663952529455
Diâmetro interior	20 mm
Diâmetro interior	0.787" inch
Diâmetro exterior	26 mm
Diâmetro exterior	1.024" inch
Espessura	16 mm
Espessura	0.63" inch
Peso	21 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE