


Casquilho de agulhas FC-25-K-NADELLA - FC-25-K-NADELLA

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/fc-25-k-nadella>

Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F ₂ mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min	Suitable needle bush
25	FC-25-K	25	32	20	66.4	8700	HK2512

Shaft Ø mm	Gapping			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Max. mm	Min. mm	Max. mm	Min. mm	
25	31.972	24.967	25.007	46	25.000	24.991	31.988	31.972	0.026

CARACTERÍSTICAS DO PRODUTO

Marca	NADELLA
Nº Ean13	3663952529479
Diâmetro interior	25 mm
Diâmetro exterior	32 mm
Espessura	20 mm
Peso	26 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE