


## Rolamento esfera carreira simple 1602-DC-NICE - 1602-DC-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/1602-dc-nice>

**1600** Series™ Precision Ground Radial Bearings **NICE**



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
1602™	DC					0.2500 6.350	0.6875 17.463
BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C <sub>0</sub> (lb) (N)	W <sup>0</sup> (lb) (g)	d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)	
0.2500 6.350	511 2274	170 757	0.02 0.01	0.330 8.38	0.614 15.60	0.012 0.30	

Width for sealed versions = 0.3125 (7.938) Weights given are for greased and sealed versions Multi-part seal see page 42

## CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	637400291211
Diâmetro interior	6.35 mm
Diâmetro exterior	17.463 mm
Espessura	7.938 mm
Peso	10 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE