


Rolamento esfera carreira simple 1620-DS-NICE - 1620-DS-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/1620-ds-nice>

1600 Series™ Precision Ground Radial Bearings **NICE**



| SUFFIX | | | | | PRINCIPLE DIMENSIONS | | |
|----------------------------|-----------------------------|---|-------------------------------|------------------------------------|------------------------------------|--------------------------------------|--------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| | | | | | | +0.000 +0.00 -0.0005 -0.013 | +0.000 +0.00 -0.0005 -0.013 |
| 1620™ | | | | | | 0.4375 11.113 | 1.3750 34.925 |
| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | | |
| WIDTH B (in) (mm) | DYNAMIC C (lb) (N) | STATIC C ₀ (lb) (N) | W ⁰ (lb) (g) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) | |
| 0.4375 11.113 | 1878 8307 | 850 3783 | 0.12 0.05 | 0.658 16.71 | 1.203 30.56 | 0.025 0.64 | |

Weights given are for greased and sealed versions

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | NICE |
| Nº Ean13 | 3663952557373 |
| Diâmetro interior | 11.113 mm |
| Diâmetro exterior | 34.925 mm |
| Espessura | 11.113 mm |
| Peso | 50 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE