


Rolamento esfera carreira simple 1640-SS-NICE - 1640-SS-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/1640-ss-nice>

1600 Series™ Precision Ground Radial Bearings (con't)



| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|----------------------------|-----------------------------|---|------------------------|------------------------------------|------------------------------------|---------------------------------------|---------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| | | | | | | +0.000 +0.000 -0.0005 -0.013 | +0.000 +0.000 -0.0005 -0.013 |
| 1640™ | | | | | SS | 0.9750 22.225 | 2.0000 50.800 |
| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | | |
| WIDTH B (in) (mm) | DYNAMIC C (lb) (N) | STATIC C ₀ (lb) (N) | W ⁰ (kg) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) | |
| 0.5625 14.288 | 2967 13203 | 1350 6008 | 0.29 0.13 | 1.113 28.27 | 1.780 44.70 | 0.035 0.89 | |

Weights given are for greased and sealed versions

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | NICE |
| Nº Ean13 | 3663952557762 |
| Diâmetro interior | 22.225 mm |
| Diâmetro exterior | 50.8 mm |
| Espessura | 14.288 mm |
| Peso | 130 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE