

Rolamento esfera carreira simple 3002-SS-NICE - 3002-SS-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/3002-ss-nice>

3000 Series® Semi-Ground Radial Bearings NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3002™				SS		+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 ⓐ
						0.2500 6.350	0.5675 17.463

WIDTH B (in) (mm)	BASIC LOAD RATINGS		WEIGHT W (lb) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)		da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.2500 ⓑ 6.350	255 1135	170 757	0.02 0.01	0.330 8.38	0.614 15.60	0.012 0.30

ⓐ Width for sealed versions = 0.3125 (7.938) ⓑ Weights given are for greased and sealed versions
ⓐ 3038 and larger +0.0005/-0.005 (-0.001/-0.125)

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952558035
Diâmetro interior	6.35 mm
Diâmetro exterior	17.463 mm
Espessura	6.35 mm
Peso	10 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE