

Rolamento esfera carreira simple
3003-SC-NICE - 3003-SC-NICE

https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/3003-sc-nice

3000 Series® Semi-Ground Radial Bearings

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

TO CLEAR r

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3003™			SC			0.3125 7.938	0.8750 22.225

BASIC LOAD RATINGS		WEIGHT		ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.2813 (7.1450)	325 (1446)	255 (1135)	0.03 (0.01)	0.474 (12.04)	0.778 (19.76)	0.012 (0.30)

① Width for sealed versions = 0.3438 (8.733)

② Weights given are for greased and sealed versions

③ 3003 and larger +.0000/-0.0006 (+/-0.002/-0.015)

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952558066
Diâmetro interior	7.938 mm
Diâmetro exterior	22.225 mm
Espessura	7.145 mm
Peso	10 g
Embalagem	1

contato@123rolamento.pt
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE