

Rolamento esfera carreira simple 3004-SC-NICE - 3004-SC-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/3004-sc-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

| SUFFIX | | | | | PRINCIPLE DIMENSIONS | | |
|---------|-------------|-------------|---------------|---------------|----------------------|------------------------------------|-------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3004™ | | SC | | | | +0.005 +0.13 -0.000 -0.00 | +0.000 +0.00 -0.015 -0.015 |
| | | | | | | 0.3750 9.525 | 0.8750 22.225 |

| BASIC LOAD RATINGS | | WEIGHT | | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|------------------------------|------------------------------|-------------------|--------------------------------|------------------------|-----------------------|
| WIDTH B (in) (mm) | DYNAMIC C (lbs) (N) | STATIC Co (lbs) (N) | W (lb) (kg) | da min (in) (mm) | Da max (in) (mm) | r max (in) (mm) |
| 0.2813 7.1450 | 325 1448 | 250 1135 | 0.03 0.01 | 0.474 12.04 | 0.778 19.76 | 0.015 0.38 |

Width for sealed versions = 0.3438 (8.733) Weights given are for greased and sealed versions
0.3038 and larger +0.0000/-0.0006 (+/-0.000/-0.15)

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | NICE |
| Nº Ean13 | 3663952558134 |
| Diâmetro interior | 9.525 mm |
| Diâmetro exterior | 22.225 mm |
| Espessura | 7.145 mm |
| Peso | 10 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE