

## Rolamento esfera carreira simple 3005-DC-NICE - 3005-DC-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/3005-dc-nice>

**3000 Series® Semi-Ground Radial Bearings** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm) +0.005 +0.13 -0.000 -0.00	O.D. D (in) (mm) +0.000 +0.00 -0.0005 -0.013
3005™	DC					0.3125 7.938	0.9063 23.020

WIDTH B (in) (mm) +0.005 +0.00 -0.005 -0.13	BASIC LOAD RATINGS		WEIGHT W (lb) (kg) 0.04 0.02	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N) 350 1558	STATIC Co (lb) (N) 300 1335		da min (in) (mm) 0.503 12.76	Da max (in) (mm) 0.778 19.76	r max (in) (mm) 0.012 0.30
0.3125 7.938	350 1558	300 1335	0.04 0.02	0.503 12.76	0.778 19.76	0.012 0.30

Ⓢ Weights given are for greased and sealed versions  
Ⓢ 3038 and larger +.0000/-0.005 (-.000/-0.13)

## CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952558158
Diâmetro interior	7.938 mm
Diâmetro exterior	23.02 mm
Espessura	7.938 mm
Peso	20 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE