

Rolamento esfera carreira simple 3007-SC-NICE - 3007-SC-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/3007-sc-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3007™					SC	+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.015 0.0063
						11.113	23.020

WIDTH		BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
B (in) (mm)	C (lbs) (N)	Co (lbs) (N)	W (lbs) (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)	
0.3125 7.938	300 1508	300 1355	0.03 0.01	0.517 13.13	0.778 19.76	0.015 0.38	

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3038 and larger +0.000/-0.006 (-0.000/-0.15)

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952558264
Diâmetro interior	11.113 mm
Diâmetro interior	7/16" inch
Diâmetro exterior	23.02 mm
Diâmetro exterior	29/32" inch
Espessura	7.938 mm
Espessura	5/16" inch
Peso	10 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE