


Rolamento esfera carreira simple

3021-SC-NICE - 3021-SC-NICE

https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/3021-sc-nice

3000 Series® Semi-Ground Radial Bearings (con't)

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT RING
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3021™			SC			+0.005 +0.13 -0.000 -0.005	+0.000 +0.00 -0.013 -0.005
						0.5000 12.700	1.3750 34.925

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.4375 11.113	940 4183	850 3783	0.11 0.05	0.720 18.29	1.203 30.56	0.025 0.64

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3028 and larger +.0000/-0.0006 (+.000/-0.015)

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952558530
Diâmetro interior	12.7 mm
Diâmetro exterior	34.925 mm
Espessura	11.113 mm
Peso	50 g
Embalagem	1

contato@123rolamento.pt
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE