

Rolamento esfera carreira simple 3023-DS-NICE - 3023-DS-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/3023-ds-nice>

3000 Series® Semi-Ground Radial Bearings (con't) NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3023™			DS			+0.005 +0.13 -0.000 -0.013	+0.000 +0.00 -0.0005 -0.013

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Ca (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.4375 11.113	940 4183	860 3783	0.10 0.05	0.753 19.13	1.203 30.56	0.025 0.64

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3023 and larger +0.0005/-0.005 (+0.002/-0.13)

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952558578
Diâmetro interior	15.875 mm
Diâmetro exterior	34.925 mm
Espessura	11.113 mm
Peso	50 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE