


Rolamento esfera carreira simple 3040-DC-NICE - 3040-DC-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/3040-dc-nice>

3000 Series® Semi-Ground Radial Bearings (con't) NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3040™	DC					+0.005 +0.13 -0.000 -0.013	+0.000 +0.00 -0.0005
						0.8750 22.225	2.0000 50.800

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.5625 14.288	1480 6598	1350 6008	0.29 0.13	1.113 28.27	1.760 44.70	0.035 0.89

Ⓢ Weights given are for greased and sealed versions
Ⓣ 3038 and larger +.0000/-0.0005 (+.000/-0.013)

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952558851
Diâmetro interior	22.225 mm
Diâmetro exterior	50.8 mm
Espessura	14.288 mm
Peso	130 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE