

## Rolamento esfera carreira simple 3040-NS-NICE - 3040-NS-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/3040-ns-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3040™						+0.005 +0.13 -0.000 -0.013	+0.000 +0.00 -0.0005 -0.013

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)	W <sup>⓪</sup> (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.5625 14.288	1480 6598	1350 6008	0.29 0.13	1.113 28.27	1.760 44.70	0.035 0.89

<sup>⓪</sup> Weights given are for greased and sealed versions  
<sup>⓪</sup> 3038 and larger +.0000/-0.0005 (+.000/-0.013)

## CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952558899
Diâmetro interior	22.225 mm
Diâmetro exterior	50.8 mm
Espessura	14.288 mm
Peso	130 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE