

# Rótula TSM MB-M14-DUNLOP - MB-M14-DUNLOP

<https://www.123rolamento.pt/rolamento-mancal/rotula/tsm/mb-m14-dunlop>

MALE ROD ENDS 



**MB SERIES: MB - MBS - MB SS**

**Description:**  
MB Series is our 3-piece standard range of maintenance required general purpose male rod ends suitable for medium heavy industrial/mechanical load applications requiring low friction and good wear resistance, available in both metric and imperial bore and thread sizes. An oil impregnated sintered bronze race is also available for some sizes or if quantity justifies production, suitable for high precision motion transfer applications and extended wear life.

**Material Specifications:**  
Housing: Steel 230M07PB and forged 083M44, zinc plated and clear trivalent passivate and stainless steel 303L 304. Forged. Race: Bronze SAE660 and oil impregnated sintered bronze. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated and stainless steel 440C. Stud: Steel 230M07PB zinc plated and clear trivalent passivate and stainless steel 303L.

**Features:**  
Metric & imperial thread & bore sizes  
Low friction  
Self-lubricating option available  
Extended wear life  
Maintenance required  
Studded option

**Possible Applications:**  
Medium/heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment  
Recreational vehicles  
Precision equipment

**Temperature Range:**  
-34°C to +143°C

**Specifications:**  
ELV & RoHS compliant

**Housing:** Steel 230M07PB (Sizes MB3 - M12), Forged 083M44 (Sizes M14 - M25), Zinc Plated and Clear Trivalent Passivate

**Race:** Bronze SAE660

**Ball:** Bearing Steel 100Cr6, Case Hardened Electro-less Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MB-M14		14	M14X2.00	19	13.50	34	40	36	16.80	22,125

**Interchange table**

Dunlop	Rose	Tuthill	Alinabal	SKF	Asahi	IKO	Fluro
MB-M (metric)	MM	MB-M	MM-M	SARAC-M	JAM	POS	GAS
MB (imperial)	RM-U	MB	VM-D	-	-	POSB	-

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.  
For stainless steel add 'SS' to part no. For example 'MB-M03 SS'

## CARACTERÍSTICAS DO PRODUTO

Marca	DUNLOP
Nº Ean13	3663952559766
Diâmetro interior	14 mm
Diâmetro exterior	34 mm
Espessura	19 mm
Tipo	SA
Linha	Rosca direita
Lubrificação	NA
Carga estática	0.0221 kN
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE