

Rolamento esfera carreira simple 7508-DL-NICE - 7508-DL-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/7508-dl-nice>

7500 Series™ Heavy Duty Precision Ground Radial Bearings

- PRECISION GRINDING ON ALL CONTACT SURFACES - EXCEPT TO THE TWO OPPOSITE SIDES
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- HEAVY DUTY BEARING - HIGH - HIGH RPM
- THERMALLY TREATED BEARING STEEL
- PRECISION GRINDING
- WIDE RETAINER STAIRS
- DOUBLE BEADED STAIRS
- PRECISE OPERATIVE TEMPERATURE CONTACT ROLL WITH TIGHT FITS
- AVAILABLE IN BOTH BEADED OR OPEN
- ALL BEARINGS HAVE A PUMP AND COOLANT HOLES AVAILABLE TO BE ORDERED
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION, SHAFT AND HOUSING

| BEARING | PRINCIPLE DIMENSIONS | | | | | |
|---------|----------------------------|----------------------------|----------------------------|-------------------|----------------------------------|-------------------|
| | BORE d (in) (mm) | O.D. D (in) (mm) | WIDTH B (in) (mm) | A (in) (mm) | INNER WIDTH C (in) (mm) | F (in) (mm) |
| 7508™ | +0.000 -0.005 -0.013 | +0.000 -0.005 -0.013 | +0.000 -0.005 -0.013 | 0.025 1.58 | 7500 19.05 | 1.009 25.63 |

| PRINCIPLE DIMENSIONS | | | BASIC LOAD RATINGS | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------|-------------------|-------------------|-----------------------------|---|-------------------|--------------------------------|------------------------|-----------------------|
| G (in) (mm) | H (in) (mm) | J (in) (mm) | Dynamic C (lb) (N) | Static C ₀ (lb) (N) | W (lb) (kg) | da min (in) (mm) | Da max (in) (mm) | r max (in) (mm) |
| 0.136 3.45 | 0.042 1.07 | 1.9219 48.82 | 0.035 0.89 | 8995 11548 | 0.33 4581 | 0.750 19.05 | 1.500 38.10 | 0.036 0.89 |

① When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7514™ and larger is +0.000/-0.005 (-0.001/-0.125)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of FSC Nippon Bearings.

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | NICE |
| Nº Ean13 | 3616060473271 |
| Diâmetro interior | 12.7 mm |
| Diâmetro exterior | 44.45 mm |
| Espessura | 15.88 mm |
| Peso | 150 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE