

# Rolamento esfera carreira simple 7508-DL-NICE - 7508-DL-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/7508-dl-nice>

**7500 Series™ Heavy Duty Precision Ground Radial Bearings**

- PRECISION GRINDING ON ALL CONTACT SURFACES - RESULTS IN THE LOWEST COEFFICIENT OF FRICTION
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- MAXIMUM SPEEDS - HIGH RPM
- THROUGH HARDENED BEARING STEEL
- PRECISION GRINDING
- WIDE RETAINER STAIRS
- DOUBLE SEALED VERSIONS
- EXCELLENT OPERATING TEMPERATURE RANGE - UP TO CONTACT BALLS WITH THERMAL STABILITY
- AVAILABLE IN BOTH BEALED OR OPEN
- ALL BEARINGS MEET A RULM AND ISO 9001 CERTIFIED MANUFACTURING PROCESS
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION, SHOCK AND VIBRATION ARE CONCERNS

BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	INNER WIDTH C (in) (mm)	F (in) (mm)
7508™	+0.000 -0.013	+0.000 -0.005	+0.000 -0.005	0.025 1.58	0.700 19.05	1.009 25.63

PRINCIPLE DIMENSIONS			BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
G (in) (mm)	H (in) (mm)	J (in) (mm)	Dynamic C (lb) (N)	Static C <sub>0</sub> (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.136 3.45	0.042 1.07	1.9219 48.82	0.035 0.89	8995 11548	0.33 4581	0.750 19.05	1.500 38.10	0.036 0.89

1 When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)  
 2 Tolerance for 7514™ and larger is +0.000/-0.005 (+.000/-0.15)  
 3 Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
 4 Weights given are for greased and sealed versions  
 All bearing designations listed herein are trademarks of FSC Nippon Bearings.

## CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3616060473271
Diâmetro interior	12.7 mm
Diâmetro exterior	44.45 mm
Espessura	15.88 mm
Peso	150 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE