

Rolamento esfera carreira simple 7510-DL-NICE - 7510-DL-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/7510-dl-nice>

7500 Series™ Heavy Duty Precision Ground Radial Bearings

- PRECISION GRINDING ON ALL CONTACT SURFACES - REFLECTS TO THE HIGH BEARING CAPACITY
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- HAIR GRIND BEARING - HIGH RPM
- THERMALLY TREATED BEARING STEEL
- REFINED FINISH
- WIDER RETAINER STANDARDS
- DOUBLE SEALED STANDARD
- EXCELLENT OPERATING TEMPERATURE CONTACT ROLL WITH TIGHT SLEEVES
- AVAILABLE IN BOTH BEALED OR OPEN
- ALL BEARINGS HAVE A PUMP AND COOLANT HOLES AVAILABLE TO BE ORDERED
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION, SHAFT AND HOUSING

BEARING	PRINCIPLE DIMENSIONS				
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	INNER WIDTH C (in) (mm)	F (in) (mm)
7510™	+0.000 -0.005 -0.015 0.6250	+0.000 -0.005 -0.015 1.7500	+0.000 -0.005 -0.015 0.6250	+0.000-0.005 +0.00-0.13	1.009 25.63

PRINCIPLE DIMENSIONS			BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS			
G (in) (mm)	H (in) (mm)	J (in) (mm)	Dynamic C (lba) (N)	Static C ₀ (lba) (N)	W lb (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)	
0.138 3.45	0.042 1.07	1.9219 48.82	0.035 0.89	2595 11548	1025 4561	0.29 0.13	0.875 22.23	1.500 38.10	0.036 0.89

When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLQ)
 Tolerance for 7514™ and larger is +0.000/-0.005 (+0.000/-0.125)
 Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of FSC Nippon Bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3616060473288
Diâmetro interior	15.88 mm
Diâmetro exterior	44.45 mm
Espessura	15.88 mm
Peso	130 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE