

Rolamento esfera carreira simple 7514-DL-NICE - 7514-DL-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/7514-dl-nice>

7500 Series™ Heavy Duty Precision Ground Radial Bearings NICE

- PRECISION GRINDING ON ALL CONTACT SURFACES - RESULTS IN THE LOWEST COEFFICIENT OF FRICTION
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- HEAVY DUTY BEARING - HIGH - HIGH RPM
- THERMALLY TREATED BEARING STEEL
- PRECISION GRINDING
- WIDE RETAINER STANDARD
- DOUBLE SEALED STANDARD
- EXCELLENT OPERATING TEMPERATURE CONTACT ROLL WITH TIGHT TOLERANCES
- AVAILABLE IN BOTH SEALED OR OPEN
- ALL BEARINGS HAVE A PUMP AND COOLANT HOLES AVAILABLE TO BE ORDERED
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION, SHAFT AND HOUSING

BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	INNER WIDTH C (in) (mm)	F (in) (mm)
7514™	0.8750 22.23	2.0000 50.80	0.6250 15.88	0.0625 1.59	0.7500 18.05	1.306 33.17

PRINCIPLE DIMENSIONS				BASIC LOAD RATINGS		WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
G (in) (mm)	H (in) (mm)	J (in) (mm)	R (in) (mm)	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W ⊕ (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.138 3.45	0.042 1.07	2.1563 54.77	0.035 0.89	8970 13217	1950 6008	0.36 0.16	1.125 28.58	1.750 44.45	0.036 0.89

⊕ When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
⊖ Tolerance for 7514™ and larger is +0.0001/-0.0006 (+.0001/-0.015)
⊙ Weights given are for greased and sealed versions
All bearing designations listed herein are trademarks of FSC Nippon Bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3616060473301
Diâmetro interior	22.23 mm
Diâmetro exterior	50.8 mm
Espessura	15.88 mm
Peso	160 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE