

Rolamento esfera carreira simple 400-6V-NICE - 400-6V-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/400-6v-nice>

400 Series® Single Row Unground Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size (mm)
400™	6V	0.375 +0.0005-0.000 9.53 9.22	0.875 +0.005-0.000 22.23 21.88	0.250 +0.010-0.010 6.35 6.35	0.250 Reference 6.35	14	1/8 3.18

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)
0.03 0.01	156 694	108 481	75 334	60 267	42 187	30 134

Notes
Balls - Carbon Steel Grade 200
Rings - Carbon Steel, Case Hardened
Balls - 1010 Carbon Steel, Soft
Bearings supplied prelubricated with grease

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
N° Ean13	3663952559995
Diâmetro interior	9.53 mm
Diâmetro exterior	22.23 mm
Espessura	6.35 mm
Peso	10 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE