

## Rolamento esfera carreira simple 400-20V-NICE - 400-20V-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/400-20v-nice>

**400 Series® Single Row Unground Radial Bearings** **NICE**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA					
		A	B	C	D	BALLS	
		BORE (in) (mm)	O.D. (in) (mm)	WIDTH (in) (mm)	WIDTH (in) (mm)	No.	Size
400™	20V	0.375 9.53 +0.0004-0.0008 -0.131-0.00	1.125 28.58 +0.0059-0.0000 -0.131-0.00	0.375 9.53 +0.0119-0.0110 -0.251-0.25	0.375 9.53 Reference	18	18 3.18

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
0.08 0.04	200 890	139 619	96 427	78 347	54 243	38 168

Notes  
Balls - Carbon Steel Grade 200      Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened      Bearings supplied prelubricated with grease

## CARACTERÍSTICAS DO PRODUTO

Marca	NICE
N° Ean13	3663952560045
Diâmetro interior	9.53 mm
Diâmetro exterior	28.58 mm
Espessura	9.53 mm
Peso	40 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE