


Rolamento esfera carreira simple 400-23V-NICE - 400-23V-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/400-23v-nice>

400 Series® Single Row Unground Radial Bearings **NICE**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size
400™	23V	0.312 7.92 +0.0004-0.0008 -0.131-0.00	1.281 32.54 +0.0059-0.0000 -0.191-0.00	0.312 7.92 +0.0110-0.0110 -0.251-0.00	0.312 7.92 Reference	16	5/32 3.97

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50 (N)	100 (N)	200 (N)	300 (N)	600 (N)	1200 (N)
0.09 0.04	275 1224	180 809	133 592	107 476	75 334	52 231

Notes
Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
N° Ean13	3663952560076
Diâmetro interior	7.92 mm
Diâmetro exterior	32.54 mm
Espessura	7.92 mm
Peso	40 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE