


Rolamento esfera carreira simple 5561-V-NICE - 5561-V-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/5561-v-nice>

5000 Series® Single Row. Unground Flanged Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5561™	V	0.250 6.35	0.687 17.45	0.210 5.35	0.250 6.35	0.750 19.05	0.250 6.35	0.250 6.35

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY					
		REVOLUTIONS PER MINUTE					
NO.	SIZE	50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)
10	1/8	110 490	77 343	53 238	43 191	30 134	21 93

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952560212
Diâmetro interior	6.35 mm
Diâmetro exterior	17.45 mm
2º Diâmetro exterior	19.05 mm
Espessura	6.35 mm
Peso	10 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE