


Rolamento esfera carreira simple 5543-V-NICE - 5543-V-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/5543-v-nice>

5000 Series® Single Row. Unground Flanged Radial Bearings **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5543™	V	+0.005/-0.000 +13/-00	+0.005/-0.000 +18/-00	+0.010/-0.010 +25/-25	0.040	1.000	0.088	+0.010/-0.010 0.350
		0.375 9.53	0.984 23.91	0.315 8.00	1.02	25.40	2.24	8.89

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY						
		REVOLUTIONS PER MINUTE						
NO.	SIZE	50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)	
15	1/8 3.18	0.04 0.02	167 743	118 516	80 355	65 289	45 200	32 142

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952560229
Diâmetro interior	9.53 mm
Diâmetro exterior	23.01 mm
2º Diâmetro exterior	25.4 mm
Espessura	8 mm
2ª Espessura	8.89 mm
Peso	20 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE