

## Rolamento esfera carreira simple 5881-V-NICE - 5881-V-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/5881-v-nice>

**5000 Series® Single Row Unground Flanged Radial Bearings** **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE A (in) (mm)	O.D. B (in) (mm)	WIDTH C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
5881™	V	+0.005/-0.000 +13/-00	+0.005/-0.000 +18/-00	+0.010/-0.010 +25/-25	0.062	1.500	0.125	+0.010/-0.010 +25/-25
		0.500 12.70	1.379 34.93	0.463 11.76	0.463 1.87	1.500 38.10	0.125 3.18	0.546 13.87

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY					
		REVOLUTIONS PER MINUTE					
NO.	SIZE	50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)
18	3/16	0.12	375	261	160	145	101
	4/16	0.08	1969	1181	803	648	448
							316

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

### CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952560267
Diâmetro interior	12.7 mm
Diâmetro interior	1/2" inch
Diâmetro exterior	34.93 mm
Diâmetro exterior	1 3/8" inch
2º Diâmetro exterior	38.1 mm
2º Diâmetro exterior	1 1/2" inch
Espessura	11.76 mm
Espessura	0.463" inch
2ª Espessura	13.87 mm
2ª Espessura	0.546" inch
Peso	50 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE