

Rolamento esfera carreira simple 5418-V-NICE - 5418-V-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/5418-v-nice>

5000 Series® Single Row Unground Flanged Radial Bearings (con't) **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD

BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE		O.D.		WIDTH		G
		A (in)	B (in)	C (in)	D (in)	E (in)	F (in)	
5418™	V	1.000 +0.005/-0.000 25.40	2.009 +0.005/+0.000 50.80	0.572 +0.010/-0.010 14.53	0.980 2.36	2.125 53.98	0.218 5.54	0.719 +0.010/-0.010 18.34

BALLS (in)	W (lbs)	RADIAL CAPACITY					
		REVOLUTIONS PER MINUTE					
		50 (lbs)	100 (lbs)	200 (lbs)	300 (lbs)	600 (lbs)	1200 (lbs)
17	0.30	757	525	362	293	204	142
	0.14	3369	2336	1611	1304	908	632

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952560328
Diâmetro interior	25.4 mm
Diâmetro exterior	50.8 mm
2º Diâmetro exterior	53.98 mm
Espessura	14.53 mm
2ª Espessura	18.24 mm
Peso	140 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE