

## Rolamento esfera carreira simple 616-V-NICE - 616-V-NICE

<https://www.123rolamento.pt/rolamento-mancal/rolamento-esferas/carreira-simple/616-v-nice>

**600** Series™ Unground Thrust Bearings (con't) **NICE**

- UNGROUND THRUST BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1300 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- TOP STEEL BAND OFFERS EASE OF INSTALLATION
- LOWER RING IS FREE TO ROTATE AND HAS LOOSE FIT FOR SHAFTS
- LOWER RING IS FIRED AND HAS SHAFT CLEARANCE IN THE BORE



BEARING DIMENSIONAL DATA								
BEARING	SUFFIX	A	A1	B	C	BALLS		WEIGHT (lbs) (kg)
		BORE (in) (mm)	BORE (in) (mm)	O.D. (in) (mm)	HEIGHT (in) (mm)	No.	Size (mm)	
616™	V	+0.010-0.000 +25-100 31.75	+/- .010 +25 62.5	+0.010 +79 59.53	+/- .010 +25 15.88	23	1/4 6.35	0.4 0.18

THRUST CAPACITY					
REVOLUTIONS PER MINUTE					
10 (lbs) (N)	50 (lbs) (N)	100 (lbs) (N)	250 (lbs) (N)	500 (lbs) (N)	1000 (lbs) (N)
1794 7983	1449 6448	1069 4757	579 2577	419 1865	298 1326

**Notes**  
 Balls - Carbon Steel Grade 52100  
 Washers - Carbon Steel Case Hard  
 Bands - Carbon Steel Soft  
 Bearings Oiled with a Rust Preventative  
 All Bearings Marked on Band with "Designation Nice USA" as Shown

## CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952560496
Diâmetro interior	31.75 mm
Diâmetro interior	1 1/4" inch
Diâmetro exterior	59.53 mm
Diâmetro exterior	2 11/32" inch
Espessura	15.88 mm
Espessura	5/8" inch
Peso	180 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE