


# Acessórios de mancal 7608-DL-NICE - 7608-DL-NICE

https://www.123rolamento.pt/rolamento-mancal/mancal/acessorios/7608-dl-nice

**7600 Series™ Heavy Duty Precision Ground Radial Bearings With Extended Inner Ring NICE™**

- PRECISION ENGINEERED FOR ALL CONTACT SURFACES - FINISHED TO THE TIGHTEST TOLERANCES
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE - 5000-8000 RPM
- STANDARD HARDENED
- STEEL BEARING
- STYLISH CASE STAMPING
- SHOULD BE KEPT SEPARATE
- EASILY APPLICABLE SINGLE LIP CONTACT BEARING
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A HOUSING FILLET RADIUS - THIS WILL ENHANCE LIFE IN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE HIGH SPEED, HEAVY LOADS ARE REQUIRED.



BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7608™	.5000 12.70	1.7500 44.50	0.6250 15.88	0.0625 1.59	1.0000 25.40	0.138 3.45

PRINCIPLE DIMENSIONS							BASIC LOAD RATINGS		WEIGHT
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C <sub>d</sub> (N)	Static C <sub>s</sub> (N)	W (kg)
0.042 1.07	1.922 48.82	1.982 50.33	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2096 11548	1025 4561	0.36 0.16

Ⓛ When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG) Ⓛ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
 Ⓛ Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015) Ⓛ Weights given are for greased and sealed versions  
 All bearing designations listed herein are trademarks of RBC NICE® Bearings.

## CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3616060473394
Diâmetro interior	12.7 mm
Diâmetro exterior	25.63 mm
Espessura	15.88 mm
Peso	160 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE