

## Acessórios de mancal 7611-DL-NICE - 7611-DL-NICE

<https://www.123rolamento.pt/rolamento-manca/manca/acessorios/7611-dl-nice>

**7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring** NICE

- PRECISION ENGINEERED FOR ALL CONTACT SURFACES - FINISHED TO THE TIGHTEST TOLERANCES
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000 - 8000 RPM
- TIMOTHY HARDENED
- STEEL BEARING
- STYLISH CASE STAMPING
- SHOULD BE KEPT CLEAN
- EXCELLENT APPLICABLE SINGLE LIP CONTACT SURFACES
- AVAILABLE SINGLE LIP OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHIP FUL CRATE - THIS WILL PROTECT IT IN SHIPMENT
- RECOMMENDED FOR APPLICATIONS WHERE EXCESSIVE HEAT AND VIBRATION ARE NOT A CONCERN

BEARING Ø	PRINCIPLE DIMENSIONS					
	SOBE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7611™	.8675 17.46	1.7500 44.65	0.8250 15.88	0.0825 1.50	1.000 25.40	0.138 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C <sub>d</sub> (N) (lbf)	Static C <sub>s</sub> (N) (lbf)	W (kg) (lb)
0.042 1.07	1.922 49.82	1.922 49.82	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2196 11548	1025 4581	0.30 0.14

When ordering please indicate designation and style letters of bearing desired (i.e. DL, DLG)  
Tolerance for 7613™ and larger is +0.0005-0.0006 (+0.0005-0.015)  
Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
Weights given are for greased and sealed versions  
All bearing designations listed herein are trademarks of RBC NICE® Bearings.

## CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3616060473424
Diâmetro interior	17.46 mm
Diâmetro exterior	25.63 mm
Espessura	15.88 mm
Peso	140 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE