

Acessórios de mancal 7612-DL-NICE - 7612-DL-NICE

<https://www.123rolamento.pt/rolamento-mancal/mancal/acessorios/7612-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring NICE™

PRECISION ENGINEERED FOR ALL CONTACT SURFACES - FINISHED TO THE TIGHTEST TOLERANCES

- EASY TO USE INCH DIMENSIONS
- MEDIUM LOAD
- HALE SPEED RANGE: 5000 - 8000 RPM
- THERMALLY HARDENED
- CASE HARDENED
- HYDRO-CASE STABILIZED
- SHOULD BE OILED
- EXCELLENT APPROPRIATE SINGLE LIP CONTACT SURFACES
- AVAILABLE SINGLE OR DOUBLE LIP
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A HAIR FINE FINISH - THIS WILL ENHANCE LIFE IN APPLICATIONS
- RECOMMENDED FOR APPLICATIONS WHERE SMOOTH, QUIET AND LONG LIFE ARE REQUIRED.

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7612™	.7500 19.05	1.7500 44.45	0.6250 16.00	0.0625 1.59	1.009 25.63	0.136 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C _d (lb) (N)	Static C _s (lb) (N)	W (lb) (kg)
0.042 1.07	1.922 48.82	1.982 50.37	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2996 11548	1029 4061	0.28 0.13

① When ordering please indicate designation and style letters of bearing desired (i.e. DL, DLG or DLG)
② Tolerance for 7612™ and larger is +.0000-.0006 (+.0000-.015)

③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
④ Weights given are for greased and sealed versions
All bearing designations listed herein are trademarks of RBC NICE™ Bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3616060473431
Diâmetro interior	19.05 mm
Diâmetro interior	3/4" inch
Diâmetro exterior	25.63 mm
Diâmetro exterior	1.009" inch
Espessura	15.88 mm
Espessura	5/8" inch
Peso	130 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE