

Acessórios de mancal 7614-DL-NICE - 7614-DL-NICE

<https://www.123rolamento.pt/rolamento-mancal/mancal/acessorios/7614-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't) **NICE®**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE: 5000 - 8000 RPM
- PRECISION MANUFACTURE
- SHOCK RESISTANT
- WIPER CASE STANDARD
- SHOCK RESISTANT STANDARD
- IDEALLY APPLICABLE ANGULAR CONTACT BEARING
- AVAILABLE SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL BEARINGS HAVE A SHIP CASE OPTION. THIS PRICE APPLIES TO AN OPTION.
- RECOMMENDED FOR APPLICATIONS WHERE EXACTLY SPECIFIED DIMENSIONS AND SUPERIOR QUALITY ARE REQUIRED.

BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)		F (in) (mm)	G (in) (mm)
	+0.0008 +0.000 -0.0000 -0.000	+0.0000 +0.000 -0.0005 Ø -0.013	+0.000 Ø0.00 -0.005	Ø0.00 Ø0.00	0.0625 1.308	+0.005 +0.13 -0.005 -0.13
7614™ Ø	Ø1.70 22.23	2.0350 65.83	0.6250 15.88	0.0625 1.58	1.308 33.17	0.136 3.45

PRINCIPLE DIMENSIONS							BASIC LOAD RATINGS		WEIGHT
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws (in) (mm)	Radius R (in) (mm)	Dynamic C (lb) (N)	Static C ₀ (lb) (N)	W (kg)
0.042 1.07	2.158 54.77	1.179 29.95	0.492 12.50	0.261 6.63	1/4-28	0.039 0.99	2970 13217	1350 6098	0.43 0.20

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)
 ② Tolerance for 7613™ and larger is +0.0000/-0.0005 (+0.000/-0.015)
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear
 ④ Weights given are for greased and sealed versions
 All bearing designations listed herein are trademarks of NICE® Bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3616060473455
Diâmetro interior	22.23 mm
Diâmetro exterior	33.17 mm
Espessura	15.88 mm
Peso	200 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE