


Acessórios de mancal ER10-NICE - ER10-NICE

<https://www.123rolamento.pt/rolamento-mancal/mancal/acessorios/er10-nice>

ER Series Precision Ground Radial Bearings with **NICE** Extended Inner Ring and Metric Outside Diameter

- EXCLUSIVE, HEAVY DUTY "N" SEALS
- PERMANENTLY SEALED AND PRELUBRICATED FOR LONG LIFE
- STEEL YIELD GUARD AND INNER RING LUBRICATION GROOVES PROVIDE SUPERIOR PROTECTION
- BETTER PROTECTION IN EXTREME ENVIRONMENTS
- OPTIONAL LIP-FORMING SEAL IS AVAILABLE
- LUBRICATION HOLES ALLOW FOR RE-GREASING
- TWO SHARDED CUP POINT SET SCREWS OFFER EXCELLENT RESISTANCE TO LOOSENING UNDER VIBRATORY CONDITIONS
- FULLY GRINDING, SAE 52100 CHROME ALLOY STEEL RACES
- BLACK OXIDE FINISH PROVIDES ADDITIONAL CORROSION RESISTANCE



PRINCIPLE DIMENSIONS													
BASIC BEARING NUMBER	SHAFT DIAMETER (P) (mm)	OD (mm)	WIDTH (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	J (mm)	K (mm)	M (mm)	RADIUS (mm)
ER10	5/8	1.8504	1.732	13/32	1.318	31/64	1.754	9/64	3/64	3/32	3/16	5/8	0.040
	15.88	47	26.95	17.52	8.17	12.30	28.15	3.57	1.19	2.38	4.76	15.88	1.02

RADIAL CAPACITY										WEIGHT			
O (mm)	P (mm)	3-SET SCREWS	BASIC LOAD		REVOLUTIONS PER MINUTE						W (kg)		
			RATING C (N)	STATIC LOAD Co (lbf)	50 (N)	150 (lbf)	300 (N)	500 (lbf)	1200 (N)	1500 (lbf)		2500 (N)	5000 (lbf)
0.094	2 1/16	10-32	2893	1480	921	638	508	427	319	278	250	198	0.56
2.39	52.39		12527	6368	4098	2839	2292	1900	1420	1237	1113	881	0.25

ⓘ Shaft tolerance +.0003/-0.005 (+.003/-0.13) Ⓜ For low torque version add suffix "SPF"

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952560830
Diâmetro interior	15.88 mm
Diâmetro exterior	28.18 mm
Espessura	15.88 mm
Peso	250 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE