


Acessórios de mancal ER16-NICE - ER16-NICE

<https://www.123rolamento.pt/rolamento-mancal/mancal/acessorios/er16-nice>

ER Series Precision Ground Radial Bearings with **NICE** Extended Inner Ring and Metric Outside Diameter

- EXCLUSIVE, HEAVY DUTY "N" SEALS
- PERMANENTLY SEALED AND PRELUBRICATED FOR LONG LIFE
- STEEL YIELD GUARD AND INNER RING LATHEWORK PROVIDE SUPERIOR PROTECTION
- BETTER PROTECTION IN EXTREME ENVIRONMENTS
- OPTIONAL LIP FORMER SEAL IS AVAILABLE
- LUBRICATION HOLES ALLOW FOR RE-GREASING
- TWO KNURLED OIL POINT SET SCREWS OFFER EXCELLENT RESISTANCE TO LOSING OIL UNDER VIBRATORY CONDITIONS
- FULLY GRINDING, SAE 52100 CHROME ALLOY STEEL RACES
- BLACK OXIDE FINISH PROVIDES ADDITIONAL RESISTANCE



PRINCIPLE DIMENSIONS														
BASIC BEARING NUMBER	SHAFT Ø	OD	WIDTH		C	D	E	F	G	H	J	K	M	RADIUS
	(in)	(in)	A (in)	B (in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)	(in)
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
ER16	1	2.0472	1.348	33.64	56.64	36.64	1.2164	0.716	3.64	3.02	7.02	3.4	0.040	
	25.40	52	34.29	73.50	71.89	15.48	18.43	18.11	92.70	74.11	177.80	86.10	1.02	

RADIAL CAPACITY										WEIGHT			
Ø	P	3-SET SCREWS	BASIC LOAD		REVOLUTIONS PER MINUTE						W		
			RATING C	STATIC LOAD C ₀	50	150	300	500	1200	1800		2500	5000
(in)	(in)		(lbf)	(N)	(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(lbf)	(kg)
0.141	2.1784	1/4-28	3145	1770	1012	702	557	489	351	308	274	218	0.86
3.38	57.50		13965	7877	4533	3124	2479	2167	1562	1360	1219	970	0.31

Shaft tolerance +.0002/-0.005 (+.0003/-0.13) For low torque version add suffix "SFR"

CARACTERÍSTICAS DO PRODUTO

Marca	NICE
Nº Ean13	3663952560854
Diâmetro interior	25.4 mm
Diâmetro exterior	33.73 mm
Espessura	19.05 mm
Peso	310 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE