

Rótula TSM MS-08-F-DUNLOP - MS-08-F-DUNLOP

<https://www.123rolamento.pt/rolamento-mancal/rotula/tsm/ms-08-f-dunlop>

MALE ROD ENDS 



MS SERIES: MS - MSS - MS SS

Description:
MS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 230M07Ph and forged 608MA, zinc plated and clear trivalent passivate and stainless steel 303, and forged 304. Inner Ring: Steel 670M20 zinc plated and clear trivalent passivate. Liner: High strength PTFE bronze mesh composite. Ball: Bearing steel 100C6, heat treated, polished & electroless nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, high shock loads, Extended wear life, No maintenance, Studded and stainless steel options.

Possible Applications:
Medium heavy industrial mechanical applications, Construction equipment, Agricultural equipment, Motor sport and recreational vehicles requiring high precision motion control.

Temperature Range:
-200°C to +250°C

Specification:
ELV & RoHS compliant

Housing: Steel 230M07Ph (Sizes 04 - 07) Forged 608MA (Sizes 08-12) Zinc Plated and Clear Trivalent Passivate

Inner Ring: Steel 670M20, Zinc Plated and Clear Trivalent Passivate

Balls: Bearing Steel 100C6, Case Hardened and Electro-less Nickel Plated

Liners: High Strength PTFE Composite

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MS-08F		1/2	1/2 BSF	0.425	0.500	1.375	2.438	1.500	17.75	23,600

Interchange table

Dunlop	Rose	Aurora	Askubal	SKF	ASAHI	IKO	Fluro
MS-M (metric)	MHC	MM-M-T and MB-M-T	KA-P	SAKB-P	JAM-EC	POS-EC	GASW
MS (imperial)	RMC	MM-T and MB-T	-	-	-	POSB-EC	-

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

For stainless steel add 'SS' to part no. For example 'MS-04 SS'

CARACTERÍSTICAS DO PRODUTO

Marca	DUNLOP
Nº Ean13	3616060549525
Diâmetro interior	12.7 mm
Diâmetro exterior	34.925 mm
Espessura	15.875 mm
Tipo	TSM
Linha	Rosca direita
Lubrificação	com
Carga estática	0.0236 kN
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE