

Rótula TSM

MSLX-M10-8-DUNLOP - MSLX-M10-8-DUNLOP

https://www.123rolamento.pt/rolamento-mancal/rotula/tsm/mslx-m10-8-dunlop

MALE ROD ENDS 



MSX SERIES

MALE ROD ENDS

Description:
MSX series is our 3-piece steel on steel high strength range of male rod ends designed for motorsport and heavy industrial mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the inner member, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 708M20, heat treated, zinc plated and clear trivalent passivate. Inner Ring: Steel 070M20, zinc plated and clear trivalent passivate and stainless steel 304. Liner: High strength PTFE bronze mesh composite. Ball: 100Cr6 heat treated, polished and electroless Nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes. Low friction, high shock loads. Extended wear life. No maintenance. Studded and stainless steel options.

Possible Applications:
Medium/heavy industrial/mechanical applications. Construction equipment. Agricultural equipment. Motor sport and recreational vehicles requiring high precision motion control.

Temperature Range:
-200°C to +260°C

Specification:
EN & JIS compliant

Housing: Steel 708M20, Heat Treated, Zinc Plated and Clear Trivalent Passivate
Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate
Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Liner: High Strength PTFE Composite
Temp Range: -200°C to +260°C

Part No. Right Hand	Part No. Left Hand	Bore size	Thread	W	H	D	L1	L2	Static Load Rating (Newtons) Radial
	MSLX-M10-8	8	M10x1.50	14	10.50	28	48	29	31500

Interchange table

Dunlop	Aurora	Fluro
MSX MS-M (metric)	AM-M-T and AB-M-T	GAXSW
MSX MS (imperial)	AM-T and AB-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTERÍSTICAS DO PRODUTO

Marca	DUNLOP
Nº Ean13	3616060549808
Diâmetro interior	8 mm
Diâmetro interior	0.315" inch
Diâmetro exterior	14 mm
Diâmetro exterior	0.551" inch
Espessura	10.5 mm
Espessura	0.413" inch
Tipo	TSM
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE