

# Rótula TSM MXL-05-4-DUNLOP - MXL-05-4-DUNLOP

<https://www.123rolamento.pt/rolamento-mancal/rotula/tsm/mxl-05-4-dunlop>

**MALE ROD ENDS** **DUNLOP**

**DUNLOP**  
**MALE ROD ENDS**

**MX SERIES**

**Description:**  
MX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

**Material Specifications:**  
Housing: S17M 40, heat treated to 85/90 tons/m<sup>2</sup> tensile, Phosphated all over.  
Ball: 100Cr 6, heat treated, Phosphated all over.

**Features:**  
Metric and Imperial sizes available  
Can be used in application involving shock loading and high frequency oscillation.

**Possible Applications:**  
Medium / heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment and motor sport.

**Temperature Range:**  
-40°C to +150°C

**Specification:**  
ELV & RoHS compliant

**Housing:** Forged S17M40, Heat Treated to 85/90 tons/m<sup>2</sup> tensile and Phosphated all over. **Balls:** Bearing Steel 100Cr6, Heat Treated and Phosphate all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	M	X	Static Load Rating (Newtons) Radial
	MXL-05-4	20.00	3.75	3.20	3.75	31.2	1.625	1.662	3/16 UNF	22	11770

**Interchange table**

Dunlop	Rose	NMB
MXL (Metric)	RRL-M	RRL-M
MX (Imperial)	RRL	RRL

Note: Manufacturer's part numbers are used for descriptive purposes only and may not be direct equivalent products.  
'0' in part number denotes grease nipple is fitted.

## CARACTERÍSTICAS DO PRODUTO

Marca	DUNLOP
Nº Ean13	3616060550859
Diâmetro interior	6.35 mm
Diâmetro exterior	20.624 mm
Espessura	9.525 mm
Tipo	TSM
Linha	Rosca direita
Lubrificação	com
Embalagem	1
Padrão	Nenhuma norma

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE