


# Rótula SI FX-M08-DUNLOP - FX-M08-DUNLOP

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/fx-m08-dunlop>

FEMALE ROD ENDS 



**FX SERIES**

**Description:**  
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

**Material Specifications:**  
Housing: S17M 4J, heat treated to 80/90 tons/in<sup>2</sup> tensile. Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

**Features:**  
Metric and Imperial sizes available. Can be used in application involving shock loading and high frequency oscillation.

**Possible Applications:**  
Medium / heavy industrial/mechanical applications. Construction equipment. Agricultural equipment and motor sport.

**Temperature Range:**  
-40°C to +150°C

**Specification:**  
ELV & RoHS compliant

**Housing:** Forged S17M4J, heat treated to 80/90 tons/in<sup>2</sup> tensile all over. **Ball:** Bearing Steel 100Cr6, Heat Treated and Phosphate all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	J	M	X	Static Load Rating (Newtons) Radial
FX-M08		8	11.0	9.5	11.0	23.8	33.2	17.0	11.1	M8 x 1.25	21	19610

**Interchange table**

Dunlop	Rose	NMB
FX-M (Metric)	RBJ-M	RBJ-M
FX (Imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## CARACTERÍSTICAS DO PRODUTO

Marca	DUNLOP
Nº Ean13	3616060555021
Diâmetro interior	8 mm
Diâmetro exterior	11 mm
Espessura	9.5 mm
Tipo	SI
Linha	Rosca direita
Lubrificação	com
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE