



Rótula SI FX-16-FG-DUNLOP - FX-16-FG-DUNLOP

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/fx-16-fg-dunlop>

FEMALE ROD ENDS 



FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 4J, heat treated to 80/90 tons/in² tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available. Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications. Construction equipment. Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M4J, Heat Treated 80/90 tons/in² tensile and Phosphated all over. Ball: Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	J	M	X	Static Load Rating (Newton) Radial
FX-16G		1.0000	1.375	1.0000	1.375	3.000	4.125	2.125	1.625	1 1/4 UNF	24	150250

Interchange table

Dunlop	Rose	NMB
FX-M (Metric)	RBJ-M	RBJ-M
FX (Imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTERÍSTICAS DO PRODUTO

Marca	DUNLOP
Nº Ean13	3616060555328
Diâmetro interior	10000 mm
Diâmetro interior	393.701" inch
Diâmetro exterior	1.375 mm
Diâmetro exterior	0.054" inch
Espessura	1 mm
Espessura	0.039" inch
Tipo	SI
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE