

Rótula SI

FXL-06-F-DUNLOP - FXL-06-F-DUNLOP

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/fxl-06-f-dunlop>

FEMALE ROD ENDS 



FX SERIES

Description:
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

Material Specifications:
Housing: S17M 40, heat treated to 80/90 tons/in² tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

Features:
Metric and Imperial sizes available. Can be used in application involving shock loading and high frequency oscillation.

Possible Applications:
Medium / heavy industrial/mechanical applications. Construction equipment. Agricultural equipment and motor sport.

Temperature Range:
-40°C to +150°C

Specification:
ELV & RoHS compliant

Housing: Forged S17M40, Heat Treated 80/90 tons/in² tensile and Phosphated all over. Ball: Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

| Part No. Right Hand | Part No. Left Hand | B | W | H | O | D | F | A | J | M | X | Static Load Rating (Newton) Radial |
|---------------------|--------------------|------|-----|-----|-----|-------|-------|-----|-----|---------|----|------------------------------------|
| FXL-06F | | 3750 | 562 | 480 | 562 | 1.218 | 1.625 | 875 | 600 | 3/8 BSF | 22 | 27140 |

Interchange table

| Dunlop | Rose | NMB |
|---------------|-------|-------|
| FX-M (Metric) | RBJ-M | RBJ-M |
| FX (Imperial) | RBJ | RBJ |

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | DUNLOP |
| Nº Ean13 | 3616060556035 |
| Diâmetro interior | 3750 mm |
| Diâmetro exterior | 562 mm |
| Espessura | 480 mm |
| Tipo | SI |
| Linha | Rosca direita |
| Lubrificação | com |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE