



# Rótula SI

## FXL-16-G-DUNLOP - FXL-16-G-DUNLOP

<https://www.123rolamento.pt/rolamento-mancal/rotula/si/fxl-16-g-dunlop>

FEMALE ROD ENDS 



**FX SERIES**

**Description:**  
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

**Material Specifications:**  
Housing: B17M 4J, heat treated to 80/90 tons/in<sup>2</sup> tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

**Features:**  
Metric and Imperial sizes available. Can be used in application involving shock loading and high frequency oscillation.

**Possible Applications:**  
Medium / heavy industrial/mechanical applications. Construction equipment. Agricultural equipment and motor sport.

**Temperature Range:**  
-40°C to +150°C

**Specification:**  
ELV & RoHS compliant

**Housing:** Forged B17M4J, Heat Treated 80/90 tons/in<sup>2</sup> tensile and Phosphated all over.

**Ball:** Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

Part No. Right Hand	Part No. Left Hand	B	W	H	O	D	F	A	J	M	X	Static Load Rating (Newton) Radial
FXL-16G		1.0000	1.375	1.0000	1.375	3.000	4.125	2.125	1.625	1 1/4 UNF	24	150250

**Interchange table**

Dunlop	Rose	NMB
FX-M (Metric)	RBJ-M	RBJ-M
FX (Imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## CARACTERÍSTICAS DO PRODUTO

Marca	DUNLOP
Nº Ean13	3616060556400
Diâmetro interior	10000 mm
Diâmetro exterior	1375 mm
Espessura	10000 mm
Tipo	SI
Linha	Rosca direita
Lubrificação	com
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE