


Rótula GE
GE80-FW-DUNLOP - GE80-FW-DUNLOP
<https://www.123rolamento.pt/rolamento-mancal/rotula/ge/ge80-fw-dunlop>

SPHERICAL BEARINGS



DUNLOP

SPHERICAL BEARINGS



GE FW SERIES

Description:
GE-FW Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction, they do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened. Ball: Bearing steel 100Cr6, case hardened and electro-less nickel plated. Liner: PTFE fabric. Seals: Polyurethane.

Features:
Metric bore sizes
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications:
Medium/heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control

Temperature Range:
-53°C to +121°C

Specifications:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened

Race: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Ball: PTFE Fabric

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newton) Radial
GE80FW		80	75	50	130	2,300,000

CARACTERÍSTICAS DO PRODUTO

Marca	DUNLOP
Nº Ean13	3616060557353
Diâmetro interior	80 mm
Diâmetro exterior	75 mm
Espessura	50 mm
Tipo	GE
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE