

# Rótula GE

## GEZ008-ES-2RS-DUNLOP - GEZ008-ES-2RS-DUNLOP

<https://www.123rolamento.pt/rolamento-mancal/rotula/ge/gez008-es-2rs-dunlop>

SPHERICAL BEARINGS **DUNLOP**

**GEZ ES SERIES**

**Description:**  
GEZ-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS<sub>2</sub> for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS<sub>2</sub>. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seats: Polyurethane.

**Features:**  
Metric bore sizes  
Low cost  
Maintenance required  
Up to 140mm bore sizes available

**Possible Applications:**  
Light to heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment  
Hydraulic applications

**Temperature Range:**  
-34°C to +121°C

**Specifications:**  
ELV & RoHS compliant

**Outer Ring:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS<sub>2</sub>.

**Balls:** Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

**Seats:** Polyurethane

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GEZ008ES-2RS	12	11.100	9.525	22.225	41,000

## CARACTERÍSTICAS DO PRODUTO

Marca	DUNLOP
Nº Ean13	3616060558039
Diâmetro interior	12.7 mm
Diâmetro exterior	22.225 mm
Espessura	11.1 mm
Tipo	GE
Linha	Rosca direita
Lubrificação	com
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE