


Rótula GE GE35-UK-DUNLOP - GE35-UK-DUNLOP

<https://www.123rolamento.pt/rolamento-mancal/rotula/ge/ge35-uk-dunlop>

SPHERICAL BEARINGS 



SPHERICAL BEARINGS

GE UK SERIES

Description:
GE-UK-Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the balls and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction. They do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6 and stainless steel 316, case hardened.
Ball: Bearing steel 100Cr6 case hardened and electro-less nickel plated and stainless steel 440C. Liner: High temperature PTFE composite.
Seals: Polyurethane.

Features
Metric bore sizes
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications
Medium/heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control.

Temperature Range
-200°C to +240°C

Specification
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Liner: High Temperature PTFE Composite

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE35UK		35	25	20	55	224,000

CARACTERÍSTICAS DO PRODUTO

Marca	DUNLOP
Nº Ean13	3616060558497
Diâmetro interior	35 mm
Diâmetro exterior	55 mm
Espessura	25 mm
Tipo	GE
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE