


Rótula GE GE110-UK-DUNLOP - GE110-UK-DUNLOP

<https://www.123rolamento.pt/rolamento-mancal/rotula/ge/ge110-uk-dunlop>

SPHERICAL BEARINGS 



SPHERICAL BEARINGS

GE UK SERIES

Description:
GE UK Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction. They do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6 and stainless steel 316, case hardened.
Ball: Bearing steel 100Cr6 case hardened and electro-less nickel plated and stainless steel 440C. Liner: High temperature PTFE composite.
Seals: Polyurethane.

<p>Features</p> <ul style="list-style-type: none"> Metric bore sizes Low friction High shock loads Extended wear life No maintenance 	<p>Possible Applications</p> <ul style="list-style-type: none"> Medium-heavy industrial mechanical applications Construction equipment Agricultural equipment Recreational vehicles High precision motion control 	<p>Temperature Range</p> <p>-200°C to +260°C</p> <p>Specification</p> <p>ELV & RoHS compliant</p>
--	---	---

Outer Ring: Bearing Steel 100Cr6, Case Hardened **Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Liner: High Temperature PTFE Composite

Part No. Uncoated	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE110UK		110	70	55	160	1,840,000

CARACTERÍSTICAS DO PRODUTO

Marca	DUNLOP
Nº Ean13	3616060558749
Diâmetro interior	110 mm
Diâmetro exterior	160 mm
Espessura	70 mm
Tipo	GE
Linha	Rosca direita
Lubrificação	com
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE