

## Casquilho de agulhas BA2420-Z-IKO - BA2420-Z-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/ba2420-z-iko>



Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed(I)	Assembled inner ring
$F_w$	$D$	$C$	$d_2$	$h_6$	$H_7$	$C$	$C_0$	rpm		
			Min.	Max.	Min.	Max.	Min.	Max.		
38.100 (1.1247405 (1 & 8))	47.625 (1.7571250)	31.75 (1.250)	38.1	38.1	47.625	38.1	39000	74200	9000 (RB 2420)	

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3616060601476
Diâmetro interior	38.1 mm
Diâmetro exterior	47.625 mm
Espessura	31.75 mm
Velocidade-limite	9000 rpm
Carga dinâmica	39 kN
Carga estática	74.2 kN
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE