

## Cola

### 609-50ML-LOCTITE - 609-50ML-LOCTITE

<https://www.123rolamento.pt/lubrificante-adesivo/adesivo/cola/609-50ml-loctite>

TITRE	Anatole
DESCRIPTION	Solventement ML/ASTM, alcoolat lubre
NOM	LOCTITE 609
CONDITIONNEMENT	375ml
APPROBATION*	

#### Description

LOCTITE® 609 is a green, high strength methacrylate ester acrylic retaining compound designed for the bonding of cylindrical fitting parts. The product cures in the absence of air between close fitting metal surfaces. Typical applications include rotor to shafts in fractional and subfractional horsepower motors. Locks bushings and sleeves in housings on shafts. Augments press fits.

#### Avantages

Low viscosity  
Prevents loosening and leakage from shock and vibration  
Augments press fits  
Tested to the lot requirements of Military Specification MIL-R-46082B (this is a regional approval)

#### Caractéristiques

High strength methacrylate ester acrylic retaining compound designed for the bonding of cylindrical fitting parts.



## CARACTERÍSTICAS DO PRODUTO

Marca	LOCTITE
N° Ean13	4058093028117
Tipo	-
Peso	83 g
Embalagem	-
Utilize	-

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE